

SECTION 06 10 00 – Rough Carpentry

Document revision history: 08/2019 – Original Publication

Date	Section	Description of Change

PART 1 – GENERAL**1.1 Summary**

- a. Design teams will be notified at the start of a project whether or not the building and/or the scope qualifies as 'historic' and is exempt from any following item(s).
- b. Use of FSC wood is encouraged and in appropriate applications.
- c. Non-formaldehyde materials only.

1.2 Submittals

- a. Not applicable.

1.3 Qualifications

- a. Not applicable.

PART 2 – PRODUCTS**2.1 Materials**

- a. No particle board is to be used in underlayment or exterior applications.
- b. Plywood sheathing only.

PART 3 – EXECUTION**3.1 Installation**

- a. Interior dividing walls must continue to building structure.

3.2 Interface with other products

- a. Not applicable.

3.3 Testing

- a. Not applicable.

3.4 Training

- a. Not applicable.

SECTION 06 40 00 – Architectural Woodwork

Document revision history: 08/2019 – Original Publication

Date	Section	Description of Change

PART 1 – GENERAL**1.1 Summary**

- a. Design teams will be notified at the start of a project whether or not the building and/or the scope qualifies as ‘historic’ and is exempt of any following item(s).
- b. Species, profiles, trims, etc. are to match throughout the building; new and existing construction.

1.2 Submittals

- a. Any custom profiles, trims, etc. require delivery of a copy of the knife to the Owner’s Representative for future use; transmittal required with as-built requirements.

1.3 Qualifications

- a. Not applicable.

PART 2 – PRODUCTS**2.1 Materials**

- a. Use of Teak and hardwoods is preferred for longer life and in appropriate applications.
- b. Casework and custom woodwork shall be to an AWI Custom grade.
- c. Standard ‘off-the-shelf’ trim types are preferred vs. specialty, except for historic applications.
- d. Extra trim of specialty types are to be provided with overstock at the end of project.

PART 3 – EXECUTION**3.1 Installation**

- a. Where interior benches without backs are installed and the adjacent wall acts as the ‘seatback’, the wall must be detailed and/or reinforced so that frequent use, backpacks, etc. do not create damage to the wall.
- b. No wood is to be used on the exterior face of exterior doors and windows.
- c. No wood window frames allowed but for historic preservation/restoration purposes only.
- d. With the exception of ‘scribe-to-fit’ items, fabricate and finish all components off-site.

3.2 Interface with other products

- a. Casework for Recycling Collection:
 - Must be designed for use with collection inserts/receptacles but may vary in detail and aesthetics. Beyond those features, standardization is required in terms of the number of inserts and casework dimensions.
- b. See Section 11 80 00 – Solid Waste Handling Equipment for Bagit System information and images.
- c. Coordinate recycling collection station sizes with Owner. Refer to Section 11 80 00 for design standards.

3.3 Testing

- a. Not applicable.

3.4 Training

- a. Not applicable.